



Photo Emission Tech., Inc.

760 Calle Plano, Camarillo, CA 93012, USA

Tel: (805) 482-5200 • Fax: (805) 482-5252

Email: pet@photoemission.com

300 WATT SOLAR SIMULATOR

FEATURES

- Separate Lamp Housing and Power Supply/Controller
- Lamp life display
- Manual / automatic shutter control
- Constant Current Control
- Provisions for using Light Guide
- External lamp alignment
- Safety Interlock Override Warning
- Forced Air Cooling
- External Controls:
 - Lamp On/Off
 - Manual closing/opening of shutter
 - Activate timer circuit to open shutter for set exposure time.
- Output Signals:
 - Lamp “ON” Signal
 - “Shutter Open” Signal

TECHNICAL SPECIFICATIONS

<i>FEATURE DESCRIPTION</i>	<i>SPECIFICATION</i>
LIGHT SOURCE UNIT	
Type of lamp	Xenon Short Arc
Lamp Power	300 W
Light Source	Steady State
Light Delivery	5mm Diameter Light Guide
Air Mass	AM1.5G Standard: AM1.5D or AM1 optional
Lamp lifetime	1000 Hours
Dimensions (Height x Width x Depth)	11.6" (295mm) x 10.5" (267mm) x 18.5" (470mm)
Weight	22 Lbs. (10 Kg)
POWER SUPPLY UNIT	
Phase/Voltage/Frequency	Single Phase/110-220 Volts/50-60Hz
Max. Power Consumption (W)	0.7 KVA
Dimensions (Height x Width x Depth)	11.6" (295mm) x 10.5" (267mm) x 13.5" (343mm)
Weight	13 Lbs. (6 Kg.)