



Photo Emission Tech., Inc.

760 Calle Plano, Camarillo, CA 93012 USA

Tel: (805) 482-5200 Fax: (805) 482-5252

Email: pet@photoemission.com

SOLAR SIMULATOR MODEL # SS150ABA

FEATURES

- Light intensity feedback for stable output intensity
- Micro-Processor based Controller
- Host computer interface
- Lamp life display
- Manual / automatic shutter control with programmable shutter timer 0.1 sec. to 999 sec.
- External lamp alignment
- External shutter control
- Forced air cooling
- Light intensity meter
- Lamp current meter
- Selectable and adjustable constant intensity or constant lamp current
- Safety Interlock override warning

TECHNICAL SPECIFICATIONS

<i>FEATURE DESCRIPTION</i>	<i>SPECIFICATIONS</i>
LIGHT SOURCE UNIT	
Type of lamp	Xenon Short Arc
Lamp Power	1,000 W
Max. Illuminated area	5.91" (150mm) x 5.91" (150mm)
Light Source	Steady State
Air Mass	AM1.5G standard: AM0 or AM1 optional
Lamp lifetime	1000 Hours
Adjustment Range of light intensity	100 mW/cm ² +/- 15%
Simulator class as per ASTM E927	B
Spectral Match to ASTM E927	+/-25% or better
Non-uniformity of irradiance as per ASTM E927	≤3% or better
Temporal Stability as per ASTM E927	≤2% or better
Dimensions (Height x Width x Depth)	63.0 (1,600mm) x 16.4" (417mm) x 24.4" (595mm)
Weight	150 Lbs. (68 Kg)
CONTROLLER UNIT	
Phase/Voltage/Frequency	Single Phase/110-220 Volts/50-60Hz
Max. Power Consumption	2.0 KVA
Dimensions (Height x Width x Depth)	8" (203mm) x 14.5" (368mm) x 14.5" (368mm)
Weight	25 Lbs. (11.3 Kg.)