



Photo Emission Tech., Inc.

760 Calle Plano, Camarillo, CA 93012 USA

Tel: (805) 482-5200 Fax: (805) 482-5252

Email: pet@photoemission.com

SOLAR SIMULATOR MODEL # SS400AAA

FEATURES

- Light intensity feedback for stable output intensity
- Safe lamp alignment mechanism. Alignment with lamp off.
- Lamp life hour meter
- Manual / automatic shutter control with programmable shutter timer 0.1 sec. to 999 sec.
- External shutter control
- Forced air cooling
- Light intensity meter
- Lamp current meter
- Selectable and adjustable constant intensity or constant lamp current
- Over voltage warning LED
- Over current warning LED
- Shorted Lamp warning LED
- Safety Interlock override LED

TECHNICAL SPECIFICATIONS

FEATURE DESCRIPTION	SPECIFICATION
LIGHT SOURCE UNIT	
Type of lamp	Xenon Short Arc
Lamp Power	10,000 W
Max. Illuminated area	15.75" (400mm) x 15.75" (400mm)
Light Source	Steady State
Spectrum	AM1.5G Standard: AM0 or AM1 optional
Lamp lifetime	1000 Hours
Adjustment Range of light intensity	100 mW/cm ² +/- 15% (AM0:136.5 mW/cm ² +/- 15%)
Simulator class as per ASTM E927	A
Spectral Match as per ASTM E927	+/-25% or better
Non-uniformity of irradiance as per ASTM E927	≤3% or better
Temporal Stability as per ASTM E927	≤2% or better
Dimensions (Height x Width x Depth)	101.4" (2,575mm) x 43.3" (1,100mm) x 88.0" (2,235mm)
Weight	440 Lbs. (200 Kg)
POWER SUPPLY UNIT	
Phase/Voltage/Frequency	Three Phase/220 Volts/50-60Hz
Max. Power Consumption	10.0 KVA
Dimensions (Height x Width x Depth)	39.4" (1,000mm) x 31.5" (800mm) x 31.5" (800mm)
Weight	440 Lbs. (200 Kg)