



**Photo Emission Tech., Inc.**  
 760 Calle Plano, Camarillo, CA 93012 USA  
 Tel: (805) 482-5200 Fax: (805) 482-5252  
 Email: [pet@photoemission.com](mailto:pet@photoemission.com)

# SOLAR SIMULATOR MODEL # SS80AAA

## Features

- Light intensity feedback for stable output intensity
- Safe lamp alignment mechanism. Alignment with lamp off.
- Lamp life hour meter
- Manual / automatic shutter control with programmable shutter timer 0.1 sec. to 999 sec.
- External shutter control
- Forced air cooling
- Light intensity meter
- Lamp current meter
- Selectable and adjustable constant intensity or constant lamp current
- Over voltage warning LED
- Over current warning LED
- Shorted Lamp warning LED
- Safety Interlock override LED

## Technical Specifications

FEATURE DESCRIPTION	SPECIFICATION
<b>LIGHT SOURCE UNIT</b>	
Type of lamp	Xenon Short Arc
Lamp Power	300 W
Max. Illuminated area	3.15" (80mm) x 3.15" (80mm)
Light Source	Steady State
Air Mass	AM1.5G Standard: AM0 or AM1 optional
Lamp lifetime	1000 Hours
Adjustment Range of light intensity	100 mW/cm <sup>2</sup> +/- 15%
Simulator class	<b>A</b>
Spectral Match to ASTM E927	+/-25% or better
Non-uniformity of irradiance as per ASTM E927	≤2% or better
Temporal Stability as per ASTM E927	≤2% or better
Dimensions (Height x Width x Depth)	29.1" (740mm) x 11.8" (300mm) x 14.2" (360mm)
Weight	53 Lbs. (24 Kg)
<b>POWER SUPPLY UNIT</b>	
Phase/Voltage/Frequency	Single Phase/110-220 Volts/50-60Hz
Max. Power Consumption (W)	1.0 KVA
Dimensions (Height x Width x Depth)	8.3" (210mm) x 19.7" (500mm) x 14.2" (400mm)
ht	59 Lbs. (27 Kg.)